Safety Data Sheets (SDSs)

Client	CHANGZHOU JINTAN CHAOCHUANG BATTERY Co., Ltd
Add. of Client	Xiyang Village, Maolu Town, Jintan,Jiang Su
Description	Li-MnO2 Button Cell
Model /Type	CR2032
Trade Name	-
Manufacturer	CHANGZHOU JINTAN CHAOCHUANG BATTERY Co., Ltd
Add. of Manufacturer	Xiyang Village, Maolu Town, Jintan,Jiang Su
Battery parameters	3V, 210mAh
Weight of Lithium in grams	0.063g
Date of Receipt	2021-10-08

Laboratory	Dongguan ZRLK Testing Technology Co., Ltd.
Address	Building D, No.2, Jinyuyuan Mansion, No.18, Industrial West Road, Songshan Lake High-tech Industrial Development Zone, Dongguan, Guangdong, China
Approved Signatory	Barry Peng
Inspected by	Ailis.Ma
Censored by	Lahm Peng

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product name: Li-MnO2 Button Cell

Model: CR2032

Other means of identification

Synonyms:none

Recommended use of the chemical and restrictions on use

Recommended Use:Used in portabl electronic equipments;

Uses advidsed against:

a) Do not dismantle, open or shred batteries.

b) Do not expose batteries to heat or fire. Avoid storage in direct sunlight.

c) Do not short-circuit battery. Do not store batteries haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

d) Do not remove a battery from its original packaging until required for use.

e) Do not subject batteries to mechanical shock.

f) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has been made, wash the affected area with copious amounts of water and seek medical advice.

g) Observe the plus (+) and minus (–) marks on the cell, battery and equipment and ensure correct use.

h) Do not use any cell or battery which is not designed for use with the equipment.

i) Do not mix cells of different manufacture, capacity, size or type within a device.

j) Battery usage by children should be supervised.

k) Seek medical advice immediately if a cell or a battery has been swallowed.

l) Always purchase the battery recommended by the device manufacturer for the equipment.

m) Keep cells and batteries clean and dry.

n) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.

o) Use only the cell or battery in the application for which it was intended.

p) When possible, remove the battery from the equipment when not in use.

q) Dispose of properly.

Details of the supplier of the safety data sheet:

Supplier Name: CHANGZHOU JINTAN CHAOCHUANG BATTERY Co., Ltd

Address: Xiyang Village, Maolu Town, Jintan,Jiang Su

Telephone number of the supplier: 0086-18015180726

E-mail address: dudan@tenwei.com

Emergency telephone number

Company Emergency Phone Number: 0086-18015180726

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Dermal	Category 3
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Danger

Hazard statements

Toxic in contact with skin

Causes serious eye irritation

Suspected of causing cancer

Causes damage to organs through prolonged or repeated exposure



Precautionary statements-Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of water and soap

Call a POISON CENTER or doctor if you feel unwell

Take off immediately all contaminated clothing and wash it before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

harmful if swallowed. Very toxic to aquatic life with long lasting effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterixation: Mixtures

Description:

Product: Consisting of the following components.

Common Chemical Name	Concentration (%)	CAS Number
Lithium	3	7439-93-2
Propylene Carbonate	10	108-32-7
Manganese Dioxide	29	1313-13-9
Dimethoxymethane	7	109-87-5
Lithium Perchlorate	3	7791-03-9
Graphite	6	7782-42-5
Iron	42	7439-89-6

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

4. FIRST-AID MEASURES

First aid measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO2, dry chemical powder, water spray.

Unsuitable Extinguishing Media:No information available.

Specific Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide(CO)

Carbon dioxide

Other irritating and toxic gases.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

Special hazards arising from the substance or mixture:

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150℃), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.
Wash thoroughly after handling. Use this material with adequate ventilation.
The product is not explosive.

Conditions for safe storage, including any incompatibilities

If the 3V Lithium Manganese Dioxide Button Cell is subject to storage for such a long term as more than 3 months, it is recommended to recharge the 3V Lithium Manganese Dioxide Button Cell periodically.
3 months: -10℃~+40℃, 45 to 85%RH
And recommended at 0℃~+35℃ for long period storage.
Do not storage 3V Lithium Manganese Dioxide Button Cell haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.
Keep out of reach of children.
Do not expose 3V Lithium Manganese Dioxide Button Cell to heat or fire. Avoid storage in direct sunlight.
Do not store together with oxidizing and acidic materials**.**
Keep ignition sources away- Do not smoke.
Store in cool, dry and well-ventilated place.

Incompatible Products None known.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

CAS Number	ACGIH	NIOSH	OSHA
7782-42-5	TLV-TWA 2mg/m^3	RELs-TWA2.5mg/m^3	PELs-TWA 15mppcf
1333-86-4	TLV-TWA 3mg/m^3	RELs-TWA3.5mg/m^3	PELs-TWA 3.5mg/m^3
1313-13-9	PELs-TWA 0.1mg/m^3 PELs-TWA 0.02mg/m^3	N/A	N/A

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/Face Protection:



Tightly sealed goggles

Body protection:

Protective work clothing.

Skin protection:



Protective gloves

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Form: Button	
	Color: Silvery	
	Odour: Odourless	
	Odor Threshold: No information available	
Change in condition:		
pH, with indication of the concentration		Not determined.
Melting point/freezing point		Not determined.
Initial boiling point and Boiling range:		Not determined.
Flash Point		Not determined.
Evaporation rate		Not determined.

Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapor Pressure:	Not determined.
Vapor Density:	Not determined.
relative density:	Not determined.
Solubility in Water:	Not determined.
Solubility in other solvents	Not determined.
n-octanol/water partition coefficient	Not determined.
Auto-ignition temperature	Product is not self-igniting.
Decomposition temperature	Not determined.
Odout threshold	Not determined.
Evaporation rate	Not determined.
Viscosity	Not determined.
Other Information	:
Voltage	3.0V
Electric capacity	210mAh
Lithium content	0.055g

10. STABILITY AND REACTIVITY

Reactivity: Stable under recommended storage and handling conditions (see section 7, Handling and storage).

Chemical stability: Stable under normal conditions of use, storage and transport.

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Possibility of Hazardous Reactions: None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to avoid: Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids.Base metals.

Hazardous Decomposition Products: Carbon oxides, Other irritating and toxic gases.

11. TOXICOLOGICAL INFORMATION

Acute toxiciy: No data available.

LD/LC50 values relevant for classification:
Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

CMR effects(carcinogenity, mutagenicity and toxicity for reproduction): No information available.

12. Ecological Information

Toxicity:

Acquatic toxicity:
No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

Land transport

ADR/RID class: Not regulated.

UN-Number: UN3090 or UN3091.

Maritime transport

IMDG Class: Class 9.

UN Number: UN3090 or UN3091.

Marine pollutant: No

Air transport

ICAO/IATA Class: Class 9

UN/ID Number: UN3090 or UN3091

Environmental hazards: Not applicable.

Special precautions for user: Not applicable.

Transport/Additional information: Not restricted goods according to the above specifications.

The 3V Lithium Manganese Dioxide Button Cell had been tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3;

The lithium ion batteries according to Section II of PACKING INSTRUCTION 968, or Section II of PACKING INSTRUCTION 969～970 of the Dangerous Goods regulations 60th Edition may be transported. The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

Meets requirements of Special Provision 188 of IMDG(39-18) to be transported as non-dangerous goods

Meets the requirements of 49CFR173.185 to be transported as non-dangerous goods for road, rail, air, and vessel (Effective August 6, 2014 per HM224F)

The package must be handled with care and that a flammability hazard exists if the package is damaged;

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

Authorisations: No information available.

Restrictions on use: No information available.

Regulatory information

CAS No.	EU (EINECS)	**US (TSCA)**	**Japan (ENCS)**	**Canada (DSL/ NDSL)**	**Austrlia (AICS)**	**Korea (ECL)**	**China (IECSC)**
231-102-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
203-572-1	Listed	Listed	Listed	DSL	Listed	Listed	Listed
215-202-6	Listed	Listed	Listed	DSL	Listed	Listed	Listed
203-714-2	Listed	Listed	Listed	DSL	Listed	Listed	Listed
232-237-2	Listed	Listed	Listed	DSL	Listed	Listed	Listed
231-955-3	Listed	Listed	Listed	DSL	Listed	Listed	Listed
231-096-4	Listed	Listed	Listed	DSL	Listed	Listed	Listed

Chemical safety assessment A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

R20/22: Harmful by inhalation and if swallowed.

R36: Irritating to eyes.

H302: Harmful if swallowed.

H332: Harmful if inhaled.

**********End of SDS**********