SAFETY DATA SHEET
NANO TECH MOTORCYCLE CLEANERR

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name NANO TECH MOTORCYCLE CLEANER

Product number 664, 664CTJ, 667, 996, 251, 664DE, 664ES

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Detergent.

1.3. Details of the supplier of the safety data sheet

Supplier **Company name: Muc-Off Ltd**

UK - Muc-Off Ltd, Unit 23 Branksome Business Park, Bourne Valley Road, Poole, Dorset, BH12 1DW

EU- Muc-Off Ltd, Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork, Ireland, T23 AT2P

Tel: +44(0)1202 307790 **Email:** info@muc-off.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1202 307790 (Office Hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H319 Causes serious eye irritation.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

UFI CODE:PSX1-70CU-600W-R5PR

MOTORCYCLE CLEANER

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE **1-5%**

CAS number: 64-02-8 EC number: 200-573-9 REACH registration number: 01-2119486762-27-XXXX

Classification
Acute Tox. 4 - H302
Acute Tox. 4 - H332
Eye Dam. 1 - H318
STOT RE 2 - H373

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS **< 3**

CAS number: 68891-38-3 EC number: 500-234-8 REACH registration number: 01-2119488639-16-XXXX

Classification
Skin Irrit. 2 - H315
Eye Dam. 1 - H318
Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.

Inhalation Remove affected person from source of contamination. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion May cause stomach pain or vomiting.

Eye contact Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

MOTORCYCLE CLEANER

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Nitrous gases (NOx).

5.3. Advice for firefighters

Protective actions during firefighting Containers close to fire should be removed or cooled with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep container tightly closed. Keep only in the original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

GLYCERINE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ mist
WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

MOTORCYCLE CLEANER

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE (CAS: 64-02-8)

DNEL

Workers - Inhalation; Short term local effects: 2.5 mg/m³
Workers - Inhalation; Long term local effects: 2.5 mg/m³
Consumer - Inhalation; Short term local effects: 1.5 mg/m³
Consumer - Inhalation; Long term local effects: 1.5 mg/m³
Consumer - Oral; Long term systemic effects: 25 mg/kg/day

PNEC

- Fresh water; 2.2 mg/l
- Marine water; 0.22 mg/l
- Intermittent release; 1.2 mg/l
- Soil; 0.72 mg/kg
- STP; 43 mg/l

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

DNEL

Industry - Dermal; Long term systemic effects: 2750 mg/kg/day
Industry - Inhalation; Long term systemic effects: 175 mg/m³
Consumer - Dermal; Long term systemic effects: 1650 mg/kg/day
Consumer - Oral; Long term systemic effects: 15 mg/kg/day
Consumer - Inhalation; Long term systemic effects: 52 mg/m³

PNEC

- Fresh water; 0.24 mg/l
- Soil; 0.946 mg/kg
- STP; 10000 mg/l
- Marine water; 0.024 mg/l
- Intermittent release; 0.071 mg/l
- Sediment (Freshwater); 5.45 mg/kg
- Sediment (Marinewater); 0.545 mg/kg

GLYCERINE (CAS: 56-81-5)

Ingredient comments

WEL = Workplace Exposure Limits

DNEL

Industry - Inhalation; Long term local effects: 56 mg/m³

PNEC

- Fresh water; 0.885 mg/l
- Marine water; 0.0885 mg/l
- Intermittent release; 8.85 mg/l
- STP; 1000 mg/l
- Soil; 0.141 mg/kg
- Sediment (Freshwater); 3.3 mg/kg
- Sediment (Marinewater); 0.33 mg/kg

8.2. Exposure controls

Protective equipment



Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Neoprene. EN 374

MOTORCYCLE CLEANER

Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Pink.
Odour	Characteristic.
Odour threshold	No information available.
pH	pH (concentrated solution): 10.8 - 11.4
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	No information available.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	No information available.
Other flammability	No information available.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	1.02 @ 20°C
Bulk density	No information available.
Solubility(ies)	Soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Explosive under the influence of a flame	No information available.
Oxidising properties	No information available.

9.2. Other information

Other information	Not determined.
Refractive index	No information available.
Particle size	No information available.
Molecular weight	No information available.

MOTORCYCLE CLEANER

Volatility	No information available.
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Nitrous gases (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Acute toxicity - oral

ATE oral (mg/kg) 69,531.25

Acute toxicity - dermal

Notes (dermal LD_{50}) No information available.

Acute toxicity - inhalation

ATE inhalation (gases ppm) 175,781.25

ATE inhalation (vapours mg/l) 429.69

ATE inhalation (dusts/mists mg/l) 58.59

Skin corrosion/irritation

Animal data No information available.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

MOTORCYCLE CLEANER

Skin sensitisation No information available.

Germ cell mutagenicity

Genotoxicity - in vitro No information available.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact Causes serious eye irritation.

SECTION 12: Ecological Information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Toxicity No data available.

12.2. Persistence and degradability

Persistence and degradability The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request, or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

MOTORCYCLE CLEANER

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information This material and its container must be disposed of as hazardous waste. Do not puncture or incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.

Guidance CHIP for everyone HSG228.
Approved Classification and Labelling Guide (Sixth edition) L131.
Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

MOTORCYCLE CLEANER

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
CAS: Chemical Abstracts Service.
DNEL: Derived No Effect Level.
IATA: International Air Transport Association.
IMDG: International Maritime Dangerous Goods.
Kow: Octanol-water partition coefficient.
LC_{50}: Lethal Concentration to 50 % of a test population.
LD_{50}: Lethal Dose to 50% of a test population (Median Lethal Dose).
PBT: Persistent, Bioaccumulative and Toxic substance.
PNEC: Predicted No Effect Concentration.
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
vPvB: Very Persistent and Very Bioaccumulative.
IARC: International Agency for Research on Cancer.
MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
cATpE: Converted Acute Toxicity Point Estimate.
BCF: Bioconcentration Factor.
BOD: Biochemical Oxygen Demand.
EC_{50}: 50% of maximal Effective Concentration.
LOAEC: Lowest Observed Adverse Effect Concentration.
LOAEL: Lowest Observed Adverse Effect Level.
NOAEC: No Observed Adverse Effect Concentration.
NOAEL: No Observed Adverse Effect Level.
NOEC: No Observed Effect Concentration.
LOEC: Lowest Observed Effect Concentration.
DMEL: Derived Minimal Effect Level.

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity
Aquatic Acute = Hazardous to the aquatic environment (acute)
Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date

03/10/2017

Version number

1.002

Supersedes date

09/09/2016

SDS status

Approved.

MOTORCYCLE CLEANER

Hazard statements in full

H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Signature

Muc-Off Ltd.

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 01.12.2016 Version: 7 Revision: 01/01/2022

*
SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: Muc-Off Motorcycle Protectant**

· **Article number:** 608, 601, 640
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
· **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
· **Product category** PC24 Lubricants, greases, release products
· **Process category**
PROC7 Industrial spraying
PROC11 Non industrial spraying
· **Application of the substance / the mixture** Lubricant

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Muc-Off Ltd
UK - Muc-Off Ltd, Unit 23 Branksome Business Park, Bourne Valley Road, Poole, Dorset, BH12 1DW
· EU- Muc-Off Ltd, Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork, Ireland, T23 AT2P
· Tel: +44(0)1202 307790 Email: info@muc-off.com
· **Further information obtainable from:** Research & Development/E-mail: info@muc-off.com
· **1.4 Emergency telephone number:** During normal opening hours: Tel +44 (0) 1202 307790

*
SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
· **Hazard pictograms**



GHS02

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%
· **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
· **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P211 Do not spray on an open flame or other ignition source.

(Contd. on page 2)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 01.12.2016 Version: 7 Revision: 01/01/2022

Trade name: Muc-Off Motorcycle Protectant

(Contd. of page 1)

P280 Wear protective gloves / eye protection.
P271 Use only outdoors or in a well-ventilated area.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P403 Store in a well-ventilated place.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**
EUH066 Repeated exposure may cause skin dryness or cracking.
· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

UFI CODE:DRW1-5032-H00Y-T2PY

*
SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Active substance with propellant

· **Dangerous components:**		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1% Asp. Tox. 1, H304	50-<75%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas C, H280	2.5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas C, H280	2.5-<10%

-

· **Ingredients according to detergents guidline 648/2004/EC**	
aliphatic hydrocarbons	≥ 30%

· **Additional information:**

*
SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **After inhalation:** Supply fresh air; consult doctor in case of complaints.
· **After skin contact:** Generally the product does not irritate the skin.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** Do not induce vomiting; call for medical help immediately.
· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
· **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 3)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 01.12.2016 Version: 7 Revision: 01/01/2022

Trade name: Muc-Off Motorcycle Protectant

(Contd. of page 2)

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
· **5.3 Advice for firefighters**
· **Protective equipment:** Mount respiratory protective device.

*
SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
· **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
· **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurised containers.
· **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
· **7.3 Specific end use(s)** No further relevant information available.

*
SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
106-97-8 butane (containing < 0.1% butadiene (203-450-8))	
WEL	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 4)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 01.12.2016 Version: 7 Revision: 01/01/2022

Trade name: Muc-Off Motorcycle Protectant

(Contd. of page 3)

74-98-6 propane	
OEL	Short-term value: 3600 mg/m³, 2000 ppm Long-term value: 1800 mg/m³, 1000 ppm

· **Additional Occupational Exposure Limit Values for possible hazards during processing:**	
Oil mist	
WEL	Short-term value: 10 mg/m³ Long-term value: 5 mg/m³

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
· **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter AX/P2
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2
· **Protection of hands:**
Wear gloves for the protection against chemicals according to EN 374


Protective gloves

Solvent resistant gloves
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.5 mm
· **Penetration time of glove material**
For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye protection:**
Safety glasses


Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

(Contd. on page 5)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 01.12.2016 Version: 7 Revision: 01/01/2022

Trade name: Muc-Off Motorcycle Protectant

(Contd. of page 4)

*
SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Aerosol
Colour:	Clear
· **Odour:**	Sweetish
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44 °C
· **Flash point:**	-97 °C
· **Self-igniting:**	Product is not selfigniting.
· **Danger of explosion:**	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
· **Explosion limits:**	
Lower:	0.7 Vol %
Upper:	10.9 Vol %
· **Vapour pressure at 20 °C:**	1 hPa
· **Density at 20 °C:**	0.74 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.
· **Evaporation rate**	Not applicable.
· **Solubility in / Miscibility with water:**	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined.
· **Viscosity:**	
Dynamic:	Not determined.
Kinematic:	Not determined.
· **Solvent content:**	
Organic solvents:	89.1 %
Solids content:	0.8 %
· **9.2 Other information**	No further relevant information available.

*
SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 6)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 01.12.2016 Version: 7 Revision: 01/01/2022

Trade name: Muc-Off Motorcycle Protectant

(Contd. of page 5)

*
SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**		
Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4h	>4951 mg/l (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** Based on available data, the classification criteria are not met.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard**
May be fatal if swallowed and enters airways.

*
SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**	
Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%	
EL0 (48h)	1000 mg/l (Daphnia magna)
EL0(72h)	1000 mg/l (Pseudokirchneriella subcapitata)
LL0(96h)	1000 mg/l (Oncorhynchus mykiss (96h))

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **Ecotoxical effects:**
· **Remark:** Harmful to fish
· **Additional ecological information:**
· **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 01.12.2016 Version: 7 Revision: 01/01/2022

Trade name: Muc-Off Motorcycle Protectant

(Contd. of page 6)

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

*

SECTION 14: Transport information

· **14.1 UN-Number**	
· **ADR, ADN, IMDG, IATA**	UN1950
· **14.2 UN proper shipping name**	
· **ADR, ADN**	UN1950 AEROSOLS
· **IMDG**	AEROSOLS
· **IATA**	AEROSOLS, flammable
· **14.3 Transport hazard class(es)**	
· **ADR**	



· **Class**	2 5F Gases.
· **Label**	2.1
· **ADN**	
· **ADN/R Class:**	2 5F
· **IMDG, IATA**	



· **Class**	2.1
· **Label**	2.1
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	Void
· **14.5 Environmental hazards:**	
· **Marine pollutant:**	No
· **14.6 Special precautions for user**	Warning: Gases.
· **Danger code (Kemler):**	-
· **EMS Number:**	F-D,S-U
· **Stowage Code**	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code**	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable.

(Contd. on page 8)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 01.12.2016 Version: 7 Revision: 01/01/2022

Trade name: Muc-Off Motorcycle Protectant

(Contd. of page 7)

· **Transport/Additional information:**

· **ADR**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **Transport category**	2
· **Tunnel restriction code**	D
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **UN "Model Regulation":**	UN 1950 AEROSOLS, 2.1

*
SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** P3a FLAMMABLE AEROSOLS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

Class	Share in %
NK	75-<100

· **VOC-CH** 89.08 %
· **VOC-EU** 656.5 g/l
· **Danish MAL Code** 5-3
· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.

· **Department issuing SDS:** Research & Development
·
· **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark) LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1

(Contd. on page 9)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 01.12.2016 Version: 7 Revision: 01/01/2022

Trade name: Muc-Off Motorcycle Protectant

(Contd. of page 8)

Press. Gas C: Gases under pressure – Compressed gas
Asp. Tox. 1: Aspiration hazard – Category 1

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

*
SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: Muc-Off Motorcycle Dry Chain Lube**

· **Article number:** 649, 649US, 649DE, 604, 604US
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
· **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
· **Product category** PC24 Lubricants, greases, release products
· **Process category**
PROC7 Industrial spraying
PROC11 Non industrial spraying
· **Environmental release category**
ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
· **Application of the substance / the mixture** -

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Muc-Off Ltd
UK - Muc-Off Ltd, Unit 23 Branksome Business Park, Bourne Valley Road, Poole, Dorset, BH12 1DW

· EU- Muc-Off Ltd, Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork, Ireland, T23 AT2P

· Tel: +44(0)1202 307790 Email: info@muc-off.com

· **Further information obtainable from:** Research & Development: info@muc-off.com
· **1.4 Emergency telephone number:** During normal business hours: Tel: +44 (0)1202 307790

*
SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**


GHS02 flame

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.


GHS09 environment

Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.


GHS07

Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic

· **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P321 Specific treatment (see on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

UFI CODE:NUW1-N0SF-U00F-FE91

*
SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Active substance with propellant

· **Dangerous components:**		
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	50-<75%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%

-

(Contd. on page 3)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 2)

· **Additional information:**

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** Do not induce vomiting; call for medical help immediately.
· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
· **5.3 Advice for firefighters**
· **Protective equipment:** Mount respiratory protective device.

*
SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
· **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 3)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
· **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurised containers.
· **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
106-97-8 butane (containing < 0.1% butadiene (203-450-8))	
WEL	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
74-98-6 propane	
OEL	Short-term value: 3600 mg/m³, 2000 ppm Long-term value: 1800 mg/m³, 1000 ppm

· **DNELs**		
Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic		
Oral	DNEL Long term-systemic	149 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	149 mg/kg bw/day (Consumer)
		300 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	477 mg/m3 (Consumer)
		2,085 mg/m3 (Worker)

· **Additional Occupational Exposure Limit Values for possible hazards during processing:**	
Oil mist	
WEL	Short-term value: 10 mg/m³ Long-term value: 5 mg/m³

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

(Contd. on page 5)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 4)

· **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter AX/P2
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2
· **Protection of hands:**
Wear gloves for the protection against chemicals according to EN 374


Protective gloves

Solvent resistant gloves
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.5 mm
· **Penetration time of glove material**
For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye protection:**
Safety glasses


Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

*
SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**
· **General Information**
· **Appearance:**

Form:	Aerosol
Colour:	Whitish
· **Odour:**	Odourless
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	83-105 °C

(Contd. on page 6)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 5)

· **Flash point:**	-97 °C
· **Flammability (solid, gas):**	Not applicable.
· **Auto-ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
· **Explosion limits:**	
Lower:	0.6 Vol %
Upper:	10.9 Vol %
· **Vapour pressure at 20 °C:**	2,100 hPa
· **Density at 20 °C:**	0.69 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.
· **Evaporation rate**	Not applicable.
· **Solubility in / Miscibility with water:**	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined.
· **Viscosity:**	
Dynamic:	Not determined.
Kinematic:	Not determined.
· **Solvent content:**	
Organic solvents:	83.8 %
Solids content:	11.8 %
· **9.2 Other information**	No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*
SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic

Oral	LD50	>5,840 mg/kg (rat)
Dermal	LD50	>2,920 mg/kg (rat)
Inhalative	LC50/4 h	23.3 mg/l (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes skin irritation.

(Contd. on page 7)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 6)

· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure**
May cause drowsiness or dizziness.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard**
May be fatal if swallowed and enters airways.

*
SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**	
Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic	
EL50 (72h)	10-30 mg/l (algae)
LC50/96h	>13.4 mg/l (Fish)
EC50/48h	3 mg/l (Daphnia magna)

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **Ecotoxical effects:**
· **Remark:** Toxic for fish
· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

*
SECTION 14: Transport information

· **14.1 UN-Number**
· **ADR, ADN, IMDG, IATA** UN1950

(Contd. on page 8)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 7)

· **14.2 UN proper shipping name**

· **ADR, ADN**	UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· **IMDG**	AEROSOLS (Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic), MARINE POLLUTANT
· **IATA**	AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**	2 5F Gases.
· **Label**	2.1

· **ADN**

· **ADN/R Class:**	2 5F

· **IMDG**



· **Class**	2.1
· **Label**	2.1

· **IATA**



· **Class**	2.1
· **Label**	2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA**	Void

· **14.5 Environmental hazards:**	Product contains environmentally hazardous substances: p-mentha-1,8(9)-diene, Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic
· **Marine pollutant:**	Yes Symbol (fish and tree)
· **Special marking (ADR):**	Symbol (fish and tree)

· **14.6 Special precautions for user**	Warning: Gases.
· **Danger code (Kemler):**	-
· **EMS Number:**	F-D,S-U
· **Stowage Code**	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code**	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:

(Contd. on page 9)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 8)

·	Segregation as for the appropriate subdivision of class 2.
· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable.
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **Transport category**	2
· **Tunnel restriction code**	D
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **UN "Model Regulation":**	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

*

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **National regulations:**

Class	Share in %
NK	75-<100

· **VOC-CH** 83.80 %
· **VOC-EU** 574.0 g/l
· **Danish MAL Code** 5-3
· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Research & Development

(Contd. on page 10)

Safety data sheet
According to 1907/2006 EEC Article 31

Printing date: 18.12.2017 Version: 2 Revision: 01.01.2022

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 9)

· **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2